

ADVANCED TELEPHONE ENTRY with LIVE STREAMING VIDEO









Part Numbers:

AA1WPE VZN AA1WPE ATT

Recessed Mount Kit: ENC-WRM1001

CELLGATE EXCLUSIVES

- Streaming video telephone entry
- Voice Mail Intelligence VMI System ignores call when reaches voice mail and continues call group
- Verizon or AT&T LTE service *No VoIP fees required
- Ships with both AT&T & Verizon SIM cards
- Prop open notification if gate is left open more than 3 minutes
- Calls up to 6 video app contacts and 3 voice only numbers

W450 FEATURES

- Customer Self-activation
- 1 native 26-bit Wiegand Expansion Port
- Backlit LCD display and keypad
- 5,000 local codes and 64,000 non-local codes
- Cameras take photos on access attempts and on demand
- All transactions and photos stored on TrueCloud portal

EXCLUSIVE External Camera Options*

Up to 3 external cameras

Photos

- Taken on entry transactions and on demand
- Cloud-stored still photos

Recorded Video

- Pixel activated video stored on SD card or accessible via CellGate Technical Support
- Recording w/6-second pre-record









*See external camera sheet for more details



W450 Advantages

- Live streaming video visitor management
- Customer self-activation
- Convenient call group management
- Time/date restrictions for Wiegand credentials
- Control gates/doors on demand or on a schedule
- Manage multiple devices via CellGate TrueCloud



Dealer Benefits

- Easy 6-wire installation without external camera
- End-to-end support
- Cellular carrier and signal strength verification
- Ships with dual SIMs Verizon or AT&T (one SIM shipped live)
- Easy system and feature testing
- NEW cellular router software upgrade for post-installation signal analysis



Web Portal

Manage All Your CellGate Devices on One Dashboard

- Hosted by Microsoft Azure
- Event logs and photos with all transactions
- Create access credentials with time/date restrictions
- Manage notifications
- Administrative login privileges






- NEW: User can create access codes from the app
- Receive video/audio calls from visitors
- Open or hold open from anywhere
- Close on demand (override holds)
- Take photos from internal and external cameras







SPECIFICATIONS

External Camera Options

Bullet Cameras

4mm Fixed Focal Lens

5-64mm Varifocal Lens

2.8-12mm Varifocal Lens

Dome Camera

3-10.5mm Varifocal Lens

Internal Camera Angles:

Horizontal: 120° Vertical: 64°

Power Consumption (12v DC): 700mA

External Cam: 350mA

1 - Wiegand Expansion Port (26 bit)

2 Relays:

Contact rating: 0.5A @ 125vAC, 3A@30v DC Switching voltage: 277v AC, 220v DC Switching current: 4A

2 Digital inputs

IP65

Operating Temperature

-20°C - 55°C -4°F - 131°F

Dimensions (excluding antenna)

Height- 302mm (11.9")

Width- 156mm (6.1")

Depth- 140mm (top, 5.5")

120mm (bottom, 4.7")

Cellular Technology/Networks

LTE: AT&T and Verizon

VoIP (no additional service required)

Included in box

Watchman W450

Power supply - 5A

Magnetic switch

Installation manual & user manual

Mounts available:

Pedestal Mount

Recessed Mount (Optional Kit)

Antenna Options

L-bracket

Directional panel

Signal booster





Advanced Telephone Entry System







Part Numbers: AA1TP VZN AA1TP ATT

W410 FEATURES

- Gate can easily be controlled from app
- New low cellular plans (with or without photos)
- Customer self-activation
- 1 native 26-bit Wiegand port
- NEW: 5,000 local codes and 64,000 non-local codes
- Cameras take photos on access attempts and on demand
- All transactions and photos stored on TrueCloud portal

W410 EXCLUSIVES

- Calls up to 9 telephone numbers in 3 tiers
- Verizon or AT&T LTE service *No VoIP fees required
- Ships with both AT&T & Verizon SIM cards
- Voice Mail Intelligence VMI
 System ignores call when reaches voice mail and continues call tree
- Prop open notification If gate is left open more than 3 minutes
- TrueCloud™ web portal for administration

EXCLUSIVE External Camera Options*

Single external camera

Photos

- Taken on entry transactions and on demand
- Cloud-stored still photos

Video

- Pixel activated video stored on SD card
- Recording w/6-second pre-record





verizon√ 🅞 AT&

*See external camera sheet for more details



W410 Advantages

- Value-priced, feature-rich price point
- Choose desired rate plan (with or w/out photos)
- Convenient call group management
- Voice Mail Intelligence (VMI) = Fewer stranded visitors
- Time/date restrictions for Wiegand credentials
- Control gates/doors on demand or on a schedule
- Manage multiple devices via CellGate TrueCloud

Dealer Benefits


- Easy 6-wire installation without external camera
- End-to-end support
- Cellular carrier and signal strength verification
- Ships with live SIM
 Verizon or AT&T
- Easy system and feature testing
- New Pepwave router upgrade
 Improved analysis for cellular troubleshooting



Web Portal

Manage All Your CellGate Devices on One Dashboard

- Hosted by Microsoft Azure
- Event logs of all transactions
- Photos with access transactions (with photo rate plan)
- Create access credentials with date/time restrictions
- Manage push notifications
- Administrative login privileges



Cellgate App

- NEW: User can create access codes from the app
- Gate/doors can be opened or held open from anywhere
- Take photos on demand from internal and external cameras (with photos rate plan)
- Review historical photo and access credential use info
- Receive prop-open notifications w/ gate status





App Available at

App Store and Google Play



SPECIFICATIONS

External Camera Options – limit 1 per W410
Bullet Cameras

4mm Fixed Focal Lens

5-64mm Varifocal Lens 2.8-12mm Varifocal Lens

Dome Camera

3-10.5mm Varifocal Lens

1Built in Camera: 3mm

Internal Camera Angles:

Horizontal: 120° Vertical: 65°

Power Consumption (12v DC):

275mA (daytime), 330mA (night)

External Camera Power Consumption:

Bullet Cameras:

4mm Fixed Focal Lens:

Max Consumption-Day = 180mA Night = 400mA

5-64mm Varifocal Lens:

Max Consumption-Day = 180mA Night = 400mA

2.8-12mm Varifocal Lens:

Max Consumption- Day = 195mA Night = 480mA

Dome Camera

3-10.5mm Varifocal Lens:

Max Consumption-Day = 195mA Night = 480mA

1 Wiegand Expansion Port (26 bit): 12 volt

2 Relays:

Contact rating: .5A @ 125v AC, 2A@30v DC Switching voltage: 250v AC, 220v DC

Switching current: 2A

2 Digital inputs

IP65

Operating Temperature

-20°C - 55°C | -4°F - 131°F

Dimensions (excluding antenna)

Height- 8.3" (211mm) Width- 6.4" (163mm)

Depth- 5.5" top (140mm), 4.7" bottom (120mm)

Cellular Technology/Networks 4G/LTE: Verizon and AT&T

Included in box

Watchman W410

Power supply - 5A

Magnetic switch

Installation manual & user manual

Antenna Options

L-bracket

Directional panel

